

# HYDRAULIC DOUBLE ACTING FISHING JARS



Drilling motors and tools  
**SOKOL**

The **SOKOL Hydraulic Double Acting Fishing Jar** is designed to jar both up and down. Only left-hand jars are available. Up jarring force is controlled by the amount of the drill string tension during the hydraulic delay, and down jarring force is controlled by the slack of the drill string weight during the hydraulic delay. Fishing activities with tool rotation do not affect the jar efficiency.

PHONE +7 (342) 261-31-41 | E-MAIL [Office@pfsokol.ru](mailto:Office@pfsokol.ru) | ADDRESS Pushkarskaya str.140, 614077, Perm, Russia [www.Sokol-Motors.com](http://www.Sokol-Motors.com)

# HYDRAULIC DOUBLE ACTING FISHING JARS

Size	Max OD, mm	Length, mm	Stroke, mm	Pump open area, cm <sup>2</sup>	Min thru bore, mm	Max pull during delay, kgf	Tensile yield, kgf	Torsional limit, kgf*m	Tool joint (may be customized)
86mm (3 3/8")	86	5 400	533	38	38	22 600	63 900	600	NC 26 LH
108mm (4 1/4")	110	6 400	635	57	50	31 700	81 900	1 000	NC 31 LH
172mm (6 3/4")	176	5 900	635	153	70	86 100	325 300	3 900	NC 50 LH